

**IN THE CLAIMS**

Please amend the claims as follows.

1. (Cancelled)

<sup>1</sup>  
~~2~~ (Previously Presented) A method comprising:

selecting a transmit power level and subcarrier modulation assignments based on measured channel conditions to achieve a performance level for communications over a symbol-modulated subcarrier communication channel;

determining at least one of a desired packet error rate and a desired link data rate based on the performance level desired for an application and a data type; and

determining whether to change the transmit power level depending on whether the at least one of the desired packet error rate and the desired link data rate can be achieved based on the selected subcarrier modulation assignments and the selected transmit power level.

<sup>1</sup>  
~~2~~ (Original) The method of claim ~~2~~<sup>1</sup> further comprising generating at least one of an estimated packet error rate and an estimated link data rate for the channel based on the selected subcarrier modulation assignments and the selected transmit power level, and

wherein the determining whether to change the transmit power level is based on a comparison between the at least one of the estimated packet error rate and link data rate, and the at least one of the desired packet error rate and the desired link data rate.

<sup>5</sup>  
~~5~~ (Original) The method of claim ~~2~~<sup>1</sup>, wherein the determining the at least one of the desired packet error rate and the desired link data rate is based on whether the data type comprises voice, audio, video, gaming, internet protocol, file transfer or email data.

<sup>5</sup>  
~~6~~ (Original) The method of claim ~~4~~<sup>5</sup> wherein the determining the at least one of the desired packet error rate and the desired link data rate further comprises determining the desired

packet error rate and the desired link data rate based on a desired quality of service level for the application using data of the data type.

~~7-6.~~ (Original) The method of claim ~~2~~<sup>1</sup> further comprising:

decreasing the transmit power level to less than a maximum power level for an application that meets a predetermined quality of service level with data having at least one of a low desired data rate or a high permitted packet error rate; and

communicating at the decreased transmit power level at either a lowered link data rate selected to substantially achieve the desired packet error rate, or at an increased packet error rate selected to substantially achieve the desired link data rate.

~~8~~ ~~7.~~ (Original) The method of claim ~~2~~<sup>1</sup> further comprising:

measuring channel conditions of at least one other communication channel; and

refraining from increasing the transmit power level when an increased transmit power level would cause an unacceptable level of interference with other communication devices based on the measured channel conditions of the at least one other communication channel.

~~9~~ ~~8.~~ (Original) The method of claim ~~2~~<sup>1</sup> further comprising increasing the transmit power level to achieve at least one of a decreased the packet error rate or an increased the link data rate to substantially meet a quality of service level for the application and the data type.

~~10~~ ~~9.~~ (Original) The method of claim ~~2~~<sup>1</sup> further comprising:

refraining from increasing the transmit power level; and

either communicating at a lowered link data rate selected to substantially achieve the desired packet error rate, or communicating at a reduced packet error rate selected to substantially achieve the desired link data rate.

10. (Cancelled)

<sup>2</sup>11. (Previously Presented) The method of claim <sup>10</sup>12 wherein the selecting the subcarrier modulation assignments comprises selecting one of no modulation, BPSK modulation, QPSK modulation, 8-PSK modulation, 16-QAM, 32-QAM, 64-QAM, 128-QAM and 256-QAM for the individual subcarriers of the communication channel.

<sup>10</sup>12. (Previously Presented) A method comprising selecting a transmit power level and subcarrier modulation assignments based on measured channel conditions to achieve a performance level for communications over a symbol-modulated subcarrier communication channel,

wherein the communication channel comprises a plurality of individual symbol-modulated subcarriers, and wherein the selecting comprises selecting modulation rates for the individual subcarriers based on the measured channel conditions,

wherein the selecting the subcarrier modulation assignments comprises selecting the subcarrier modulation assignments for the individual subcarriers based on a received signal, and

wherein the method further comprises receiving data packets comprising data and training symbols modulated in accordance with the selected subcarrier modulation assignments over the plurality of subcarriers, the data packets transmitted at the selected transmit power level.

<sup>2</sup>  
<sup>3</sup>13. (Original) The method of claim <sup>2</sup>12 wherein the selecting the subcarrier modulation assignments and the generating the at least one of the estimated packet error rate and the estimated link data rate are performed by a receiving station, and

wherein the method further comprises requesting, by the receiving station, a transmitting station to change the transmit power level based on the desired packet error rate and the desired link data rate.

<sup>4</sup>  
<sup>3</sup>14. (Original) The method of claim <sup>3</sup>13 further comprising:

refraining, at the transmitting station, from increasing the transmit power level based on at least one of either network considerations, interference considerations or power consumption considerations;

reselecting the subcarrier modulation assignments to achieve a quality of service level;  
and

communicating the re-selected selecting subcarrier modulation assignments to the  
receiving station.

<sup>13</sup> 15. (Original) A method comprising:  
receiving a communication signal transmitted at a predetermined transmit power level  
carrying packets in a burst of predetermined size;  
evaluating based on characteristics of the received communication signal for various  
packet error rates, various subcarrier modulation assignments and fragment sizes to determine  
potential link data rates; and  
selecting one of the subcarrier modulation assignments and fragment sizes based on the  
potential link data rate to achieve a desired link data rate.

<sup>13</sup>  
<sup>14</sup> 16. (Original) The method of claim 15 wherein:  
the receiving the communication signal comprises receiving the communication signal  
transmitted at the predetermined transmit power level carrying packets having one of either a  
requested or a predetermined burst size; and  
the evaluating comprises evaluating the various subcarrier modulation assignments and  
fragment sizes based on measured conditions of a communication channel through which the  
communication signal is received.

<sup>13</sup>  
<sup>15</sup> 17. (Original) The method of claim 15 wherein:  
the evaluating further comprises estimating a duration of a data burst and a number of  
bytes expected to be received without error to determine an estimated link data rate, and  
wherein the selecting further comprises selecting a combination of packet error rate and  
fragment size to achieve a highest link data rate.

<sup>13</sup>  
<sup>16</sup> 18. (Original) The method of claim 15 further comprising:

transmitting the selected subcarrier modulation assignments, the selected fragment size and an expected packet error rate to a transmitting station; and

receiving subsequent communications from the transmitting station in accordance with the selections.

<sup>17</sup>  
~~19~~. (Original) The method of claim <sup>13</sup>~~15~~ wherein the communication signal is received through a communication channel comprising a plurality of individual symbol-modulated subcarriers, and wherein the selecting comprises selecting modulation rates for the individual subcarriers based on the measured conditions of the communication channel.

<sup>17</sup>  
~~18~~ 20. (Original) The method of claim ~~19~~ wherein the selecting the subcarrier modulation assignments comprises selecting at least one of no modulation, BPSK modulation, QPSK modulation, 8-PSK modulation, 16-QAM, 32-QAM, 64-QAM, 128-QAM and 256-QAM for the individual subcarriers of the communication channel,

wherein individual subcarriers having a better channel response are assigned higher-order modulation assignments having more bits per symbol, and

wherein subcarriers having a worse channel response are assigned lower-order modulation assignments having less bits per symbol.

21. (Cancelled)

<sup>9</sup>  
~~22~~. (Previously Presented) An apparatus comprising:  
an application controller to determine a desired performance level for an application and data type;

a physical layer to select a transmit power level and subcarrier modulation assignments for receipt of data over a communication channel at the desired performance level; and

a network controller to determine a desired packet error rate and a link data rate based on the desired performance,

wherein the network controller is to further determine whether to change the transmit power level for subsequent communications over the communication channel depending on

whether the desired packet error rate and link data rate can be achieved based on the selected subcarrier modulation assignments and the selected transmit power level.

<sup>19</sup> 23. (Currently Amended) The apparatus of claim<sup>19</sup> 22 wherein the network controller is to estimate a packet error rate and a link data rate for the channel based on the selected subcarrier modulation assignments and the selected transmit power level,

wherein network controller is to further determine whether to change the transmit power level is based on a difference between the estimated packet error rate and link data rate, and the desired packet error rate or desired link data rate, and

wherein the network controller is to further determine the desired packet error rate and the desired link data rate based on whether the data type comprises one of either voice, audio, video, gaming, internet protocol, file transfer or email data.

<sup>20</sup> 24. (Currently Amended) The apparatus of claim<sup>20</sup> 23 wherein the communication channel comprises a plurality of individual symbol-modulated subcarriers, and wherein the network controller is to select modulation rates for the individual subcarriers based on the measured channel conditions, and

wherein the subcarrier modulation assignments comprise one of either no modulation, BPSK modulation, QPSK modulation, 8-PSK modulation, 16-QAM, 32-QAM, 64-QAM, 128-QAM and 256-QAM for the individual subcarriers of the communication channel.

25. (Cancelled)

<sup>22</sup> 26. (Previously Presented) A system comprising:

a omnidirectional antenna to receive communications over a symbol-modulated subcarrier communication channel;

a physical layer coupled with the antenna to select a transmit power level and subcarrier modulation assignments based on channel conditions to achieve a performance level;

an application controller to determine the performance level based on an application and data type; and

a network controller to determine at least one of a desired packet error rate and a desired link data rate based on the performance level desired for the application and the data type,

wherein the network controller is to further determine whether to change the transmit power level for subsequent communications over the communication channel depending on whether the at least one of the desired packet error rate and the desired link data rate can be achieved based on the selected subcarrier modulation assignments and the selected transmit power level.

23 27. (Original) The system of claim 22 wherein:

the network controller is to instruct a transmitting station to decrease the transmit power level to less than a maximum power level for an application that meets a predetermined quality of service level with data having at least one of a low data rate data or a high packet error rate, and

the transmitting station is to communicate at the decreased transmit power level at either a lowered link data rate selected to substantially achieve the desired packet error rate, or at an increased packet error rate selected to substantially achieve the desired link data rate,

wherein the network controller is to refrain from instructing the transmitting station to increase the transmit power level when an increased transmit power level would cause an unacceptable level of interference with other communication devices based on measured channel conditions of the at least one other communication channel.

28. (Cancelled)

24 29. (Currently Amended) A computer-readable medium that stores instructions for execution by one or more processors ~~machine-readable medium that provides instructions, which when executed by one or more processors, cause said processors to perform operations~~ comprising:

selecting a transmit power level and subcarrier modulation assignments based on measured channel conditions to achieve a performance level for communications over a symbol-modulated subcarrier communication channel;

determining at least one of a desired packet error rate and a desired link data rate based on the performance level desired for an application and a data type;

determining whether to change the transmit power level depending on whether the at least one of the desired packet error rate and the desired link data rate can be achieved based on the selected subcarrier modulation assignments and the selected transmit power level;

generating at least one of an estimated packet error rate and an estimated link data rate for the channel based on the selected subcarrier modulation assignments and the selected transmit power level,

wherein the determining whether to change the transmit power level is based on a comparison between the at least one of the estimated packet error rate and link data rate, and the at least one of the desired packet error rate and the desired link data rate,

wherein the determining the at least one of the desired packet error rate and the desired link data rate is based on whether the data type comprises voice, audio, video, gaming, internet protocol, file transfer or email data, and

wherein the determining the at least one of the desired packet error rate and the desired link data rate further comprises determining the desired packet error rate and the desired link data rate based on a desired quality of service level for the application using data of the data type.

25 30. (Currently Amended) The computer-readable ~~machine-readable~~ medium of claim 29 wherein the communication channel comprises a plurality of individual symbol-modulated subcarriers, and wherein the selecting comprises selecting modulation rates for the individual subcarriers based on the measured channel conditions, and

wherein the selecting the subcarrier modulation assignments comprises selecting one of no modulation, BPSK modulation, QPSK modulation, 8-PSK modulation, 16-QAM, 32-QAM, 64-QAM, 128-QAM and 256-QAM for the individual subcarriers of the communication channel.